




WOODLINE 1B

Luxury Vinyl Tile



Creating Life On The Floor You Walk On!



JPL-101B light fir



JPL-102B grey fir



JPL-103B dusky fir



JPL-104B deep fir



JPL-105B blonde oak



JPL-106B honey oak



JPL-107B brown oak



JPL-108B husky oak



JPL-109B holm oak



JPL-110B holly oak



JPL-111B pale balsam



JPL-112B red balsam



JPL-113B fresh oak



JPL-114B orange agate



JPL-115B hawaiian koa



JPL-116B russet elm



JPL-117B live oak



JPL-118B classic oak



JPL-119B caspian oak



JPL-120B dusky oak



JPL-121B burnt oak



JPL-122B brown sugar



JPL-123B cinnamon



JPL-124B spicy cherry



DATA SHEET

JPL Floors™ luxury vinyl tile meets the below requirement :-

		Woodline 1B Luxury Vinyl Tile
Available Sizes		3" x 36" / 4" x 36" / 6" x 36" / 7.2" x 48" / 9" x 48"
Available Thickness		2.0mm / 2.5mm / 3.0mm / 4.2mm
Custom-Made Sizes / Thickness		Please contact our sales personnel for more info
Custom-Made Colour		Please contact our sales personnel for more info
Packaging		36sq ft per box for all size and thickness
Colours		24
CLASSIFICATION		
Fire Rating	EN 13501-1	Bfl-s1
	ASTM E648-08	Class 1
Toxic Fumes	EN BS 6853:1999	Passed
Smoke Density	ASTM E662-06	Passed requirement of 450 or less
PERFORMANCE		
SGBC	SGBP 4072	Very Good
Heat Stability	ASTM F1514	Passed
Light Stability	ASTM F1515	Passed
Flexibility	ASTM F137-03	Passed
Coefficient of Friction (COF)	ASTM C1028-96	Passed
Impact Insulation Class	ASTM E989-06	△IIC 6 (less than 3dB)
Anti-Bacteria Resistance (Staphylococcus aureus / E. Coli)	ISO 846:1997	Does not promote bacteria growth
TVOC	ISO 16000	Passed
Formaldehyde Emission	ASTM D5116	Passed
Chemical Resistance ASTM F925-02 (24 hrs)	5% Acetic Acid	No Change
	5% Ammonia	No Change
	5% Hydrochloric Acid	No Change
	70% Isopropyl Alcohol	No Change
	5% Phenol	No Change
	5% Sodium Hydroxide	No Change
	Bleach	No Change
	Gasoline	No Change
	Kerosene	No Change
	Mineral Oil	No Change
	Olive Oil	No Change
	Sulfuric Acid	No Change