

JPL Floors™

STONE 4A Resilient Flooring

		Stone 4A Resilient Flooring
Available Sizes		12" x 12" / 12" x 18" / 18" x 18" / 18" x 36" / 36" x 36"
Available Thickness		2.0mm / 2.5mm / 3.0mm / 4.2mm
Custom-Made Sizes / Thickness		Please contact our sales personnel for more info
Custom-Made Colour		Please contact our sales personnel for more info
Packaging		36sq ft per box for all size and thickness
Colours		16
CLASSIFICATION		
Fire Rating	EN 13501-1	Bfl-s1
	ASTM E648-08	Class 1
Toxic Fumes	EN BS 6853:1999	Passed
Smoke Density	ASTM E662-06	Passed requirement of 450 or less
PERFORMANCE		
SGBC	SGBP 4072	Very Good
Heat Stability	ASTM F1514	Passed
Light Stability	ASTM F1515	Passed
Flexibility	ASTM F137-03	Passed
Coefficient of Friction (COF)	ASTM C1028-96	Passed
Impact Insulation Class	ASTM E989-06	△IIC 6 (less than 3dB)
Anti-Bacteria Resistance (Staphylococcus aureus / E. Coli)	ISO 846:1997	Does not promote bacteria growth
TVOC	ISO 16000	Passed
Formaldehyde Emission	ASTM D5116	Passed
Chemical Resistance ASTM F925-02 (24 hrs)	5% Acetic Acid	No Change
	5% Ammonia	No Change
	5% Hydrochloric Acid	No Change
	70% Isopropyl Alcohol	No Change
	5% Phenol	No Change
	5% Sodium Hydroxide	No Change
	Bleach	No Change
	Gasoline	No Change
	Kerosene	No Change
	Mineral Oil	No Change
	Olive Oil	No Change
	Sulfuric Acid	No Change

INSTALLATION:

Installation should be carried out in accordance with local standards.

- Make sure the sub-floor is smooth, hard, clean and dry prior to installation.
- Sub-floor to be thoroughly cured and the reading of moisture should not exceed the tolerance levels.
- The material must be allowed to acclimatize 24 hours before installation in a room temperature between 18°C to 24°C.